



SPECIFICATION		
HOISTING LOAD	2.5 TON	
TESTING LOAD	3.12 TON	
LIFTING HEIGHT	Min. 3 M ~ Max 50 M	
HOISTING	SINGLE	
	SPEED	3.5 M/MIN
	MOTOR	2.0 Kw x 4 P
HOISTING	DUAL	
	SPEED	3.5/1.75 M/MIN
HOISTING	MOTOR	2.0 / 1.0 Kw x 4 / 8 P
	MOTOR	2.0 / 1.0 Kw x 4 / 8 P
POWER SUPPLY	3Ø-220~575V-60Hz 1Ø-48V, 220V-60Hz	
CONTROL VOLTAGE	1Ø-48, 110V-60Hz	
OPERATING METHOD	PUSH BUTTON TYPE	
LOAD CHAIN SPEC.	Ø7.1 x 21P x 2 FALL	
RATING	30 MIN.	
NET WEIGHT	APPROX Min. 76KG~Max. 174KG	

DIMENSIONS			
구분	양정 (LIFT)		
기준	3M~8M	8M~15M	15M~50M
C	635	725	925

NO.	DESCRIPTION	MATL.	SIZE	QTY	REMARKS
DRAWN	CHECKED				
DESIGNED	APPROVED				
TITLE OF PROJECT		2.5 TON SUSPENSION DUAL TYPE			
ELEC. CHAIN HOIST GENERAL ASSEMBLY		SCO-2500D			
SCALE	1/1				
DATE	2015. 8.				
DWG. NO.		SCO-2500D			

SCO-2500D